



LavaLux LED

PRODUCT SPECIFICATION SHEET

LED PARKING GARAGE LIGHT

PAZ-45

DESCRIPTION:

THE PAZ-45 IS A HIGH EFFICIENCY LED PARKING GARAGE LIGHT. IT IS DESIGNED TO BE SUSPENDED FROM THE PARKING GARAGE CEILING BETWEEN BEAMS. SUSPENSION HEIGHT CAN BE SPECIFIED TO MATCH GARAGE BEAM HEIGHT SUCH THAT THE FIXTURE DOES NOT PROTRUDE BELOW BEAMS. THE PAZ-45 PROVIDES MORE THAN 50% ENERGY SAVINGS OVER EXISTING CONVENTIONAL PARKING GARAGE LIGHT FIXTURES.

FEATURES:

- ✚ OVER 50% ENERGY SAVINGS
- ✚ LONG LIFE PRESENTS MAINTENANCE SAVINGS
- ✚ 70% LIGHT OUTPUT AT 50,000 HRS
- ✚ HIGH EFFICIENCY LEDs; 61 LUMENS/WATT
- ✚ EASY TO INSTALL
- ✚ CUSTOMIZABLE SUSPENSION HEIGHT TO MATCH GARAGE BEAM HEIGHT
- ✚ MADE IN THE USA



SPECIFICATIONS:

LIGHT OUTPUT	2500 LUMENS
COLOR	6500K (COOL WHITE)
INPUT VOLTAGE	100-240 VAC
INPUT FREQUENCY	50-60 HZ
INPUT POWER	41 WATTS
POWER SUPPLY SAFETY	UL 1310
OPERATING TEMPERATURE	-40 TO 120 DEG F.

OPTIONS:

- PASSIVE INFRARED SENSOR TURNS LIGHT "ON" ONLY WHEN PEOPLE ARE IN AREA
 - PROVIDES ADDITIONAL ENERGY SAVINGS
 - CAN BE MIXED WITH STANDARD MODEL FOR SAFETY

CONTACT:

LAVALUX LED
1693 MERCHANT STREET
AMBRIDGE, PA 15003
TEL: 724-624-1191
FAX: 724-266-1109
EMAIL: ASHOK.GIDWANI@LAVALUXLED.COM